


KCA TOOL BOX TALK

Falls: General Protection & Awareness



TEAMWORK
IMPROVES SAFETY

Signatures

1. _____
2. _____
3. _____
4. _____
5. _____
6. _____
7. _____
8. _____
9. _____
10. _____
11. _____
12. _____
13. _____
14. _____
15. _____
16. _____
17. _____
18. _____

Falls are the leading cause of injuries at work sites. Falls can occur from ladders, scaffolding, vehicles, heavy equipment, aerial lifts, openings, platforms, and roofs.

Here is an Example: A supervisor and three employees were placing air handler units on a third floor mezzanine during a building remodel. The supervisor was using a wheeled pry bar to lift the air handler up so the workers could place a 2-inch galvanized pipe under the air handler to serve as a roller. The supervisor was in an area about a foot from the unguarded edge and applying pressure to the pry bar toward the unguarded edge, when the pry bar slipped. The supervisor lost his balance and fell 23 feet to the cement below, causing his death.

1. How could the fatality have been prevented?
2. What safety precautions should the individual have taken? What precautions should the company have taken?

Fall Protection:

- Guardrails are required on work surfaces when workers are exposed to falls over six feet.
- Guardrails must be 42 inches high. A mid-rail is required.
- The fall protection training program must cover the recognition of potential fall hazards at the workplace for the employee.
- Body harnesses with lanyards and secure attachment points are used when guard rails cannot be provided.

For more information visit OSHA REGULATIONS: 1926.501 and 1926.503

www.KeystoneContractors.com

Teamwork Improves Safety!

Keystone Contractors Association Jon@KeystoneContractors.com 717-731-6272 # #